```
const getMovies = async () => {
  const response = await client
    .query({
      query: gql`
        query MoviesQuery {      #1
          movies {               #1
            id                   #1
            name                 #1
            year                 #1
          }                      #1
        }                        #1
      `, #1
    })
    .then((result) => result.data)
    .catch((err) => err.response);

  return response;
};

const getMovieById = async (movieId) => {
  const response = await client
    .query({
      query: gql`
        query Movie($movieId: Int!) {      #2
          movie(movieId: $movieId) {       #2
            id                             #2
            name                           #2
            year                           #2
          }                                #2
        }                                  #2
      `, #2
variables: {
  movieId,
},
    })
    .then((result) => result.data)
    .catch((err) => err.response);

  return response;
};

module.exports = {
  getMovies,
  getMovieById,
};
```

#1 The query for retrieving all movies from our GraphQL server
#2 The query for retrieving a single movie from our GraphQL server

The `getMovies` function queries our GraphQL server to retrieve all the movies. This should return the `id`, `name`, and `year`. If there are any errors, the error message is returned instead. On the other hand, the `getMovieById` function queries our GraphQL server to retrieve a single movie. It's expecting a `movieId` as a variable corresponding to the movie ID. If the movie is found, this should return the `id`, `name`, and `year` of the movie. If the movie doesn't exist, the error message is returned instead. Now that