```
const { Verifier } = require('@pact-foundation/pact');

const options = {
  provider: 'GraphQLProvider',
  providerBaseUrl: `http://localhost:4000/graphql`,
  pactBrokerUrl: process.env.PACT_BROKER_BASE_URL,
  pactBrokerToken: process.env.PACT_BROKER_TOKEN,
  providerVersion: '1.0.0',
  publishVerificationResult: true,
  consumerVersionTags: ['main'],
};

const verifier = new Verifier(options);

describe('Pact Verification', () => {
  test('should validate the expectations of GraphQLConsumer', () => {
    return verifier
      .verifyProvider()
      .then(output => {
        console.log('Pact Verification Complete!');
        console.log('Result:', output);
      });
  });
});
```

To run this test, let's add a new command to our package.json file to run the GraphQL provider verification and call the command `test:graphql:provider`:

```
 "scripts": {
    "start:provider": "cross-env PORT=3001
node provider/provider-service.js",
    "start:graphql:server": "npm run start:provider
& node graphql/provider/graphql-server.js",
    "test:graphql:provider": "npm run start:graphql:server
& jest graphql/provider/graphql-server-contract.spec.js --testTimeout=20000"
  }
```

The command `test:graphql:provider` runs the command `start:graphql:server` to start the GraphQL server as well as the movies API. When you run the `test :graphql:provider` command, you should see an output similar to figure 7.8.