Figure 8.12 The Pact Broker version of the consumer event contract with an event producer, ready for verification with the provider

At this point, the producer of the message can verify the message contract.

8.6 Kafka producer implementation

Now, we'll explain the implementation of the event provider in our example. To provide some context for the implementation, let's look at the event producer within our service. This function handles the Kafka connection, as shown in listing 8.18, constructing the event and sending the message to Kafka. The kafkajs package is imported to create the connection to the Kafka broker. The Kafka configuration takes the client ID and a list of brokers; the client ID must be unique to identify the specific producer. After configuring the Kafka connection, the producer function is then called on the Kafka object.

Listing 8.18 Movie event producer setup

```
const { Kafka } = require("kafkajs")
const { createMovie } = require("./movie.event")

const clientId = "movie-event"
const brokers = ["localhost:29092"]
const topic = "movies"

const kafka = new Kafka({ clientId, brokers })
const producer = kafka.producer()
```

Once the Kafka configuration has been set up, the event can be sent to the connected Kafka instance, as shown in listing 8.19. First, make the connection to the Kafka instance. Then, construct the message content using the `createMovie` function, as shown in listing 8.18. Finally, send the message to the Kafka topic, which takes the topic name and messages array. The message object must include a key and value that contain the movie message content.