Listing 9.3 Pact Broker docker-compose.yml

```
version: "3"

services:
  postgres:
    image: postgres
    healthcheck:
      test: psql postgres --command "select 1" -U postgres
    environment:
      POSTGRES_USER: postgres
      POSTGRES_PASSWORD: password
      POSTGRES_DB: postgres

  pact-broker:
    image: dius/pact-broker
    depends_on:
      - postgres
    environment:
      PACT_BROKER_DATABASE_USERNAME: postgres
      PACT_BROKER_DATABASE_PASSWORD: ${DB_PASSWORD}     #1
      PACT_BROKER_DATABASE_HOST: postgres
      PACT_BROKER_DATABASE_NAME: postgres
      PACT_BROKER_BASIC_AUTH_USERNAME: prescott
      PACT_BROKER_BASIC_AUTH_PASSWORD: ${BROKER_PASSWORD}     #2
      PACT_BROKER_BASIC_AUTH_READ_ONLY_USERNAME: cruz
      PACT_BROKER_BASIC_AUTH_READ_ONLY_PASSWORD:
      ${BROKER_READ_PASSWORD}             #2
      PACT_BROKER_LOG_LEVEL: INFO
      PACT_BROKER_DATABASE_CONNECT_MAX_RETRIES: "10"
    ports:
      - "92:80"
```

#1 The environment variable needs to be set for the database.
#2 The environment variable needs to be set for the Pact Broker credentials.

Once the docker-compose.yml has been created in the root of the project, the `up` command can be run to start the services shown in the following listing.

Listing 9.4 Docker compose command

```
docker compose up -d
```

When the images have been pulled and downloaded from Docker Hub, then the processes will run to start the PostgreSQL service. When the health check for the service is successful, then the Pact Broker service will start up. Once both have been started successfully, Pact Broker will be available at localhost on port 92 (`http://localhost:92`). Navigating to the URL should show the Pact Broker home screen with an example contract. As shown in figure 9.15, the docker version provides the core functionality of Pact Broker only.