The first argument after the `repo add` command is the name given to the charts, followed by the URL where the charts are stored.

Listing 9.6 The `helm repo add` command

```
helm repo add kube https://almorgv.github.io/helm-charts/charts
```

Then, install the pact-broker Helm chart from the repository that was added by using the `install` command shown in listing 9.7. The first argument after `install` states the name of the Kubernetes cluster, followed by the location of the Pact Broker Helm charts.

Listing 9.7 The `helm install` command

```
helm install pact-broker kube/pact-broker
```

If the command runs successfully, the terminal output should be similar to figure 9.17.

```
NOTES:
1. Get the application URL by running these commands:
  export POD_NAME=$(kubectl get pods --namespace default -l "app.kubernet
ance=pact-broker" -o jsonpath="{.items[0].metadata.name}")
  export CONTAINER_PORT=$(kubectl get pod --namespace default $POD_NAME -
tainerPort}")
  echo "Visit http://127.0.0.1:8080 to use your application"
  kubectl --namespace default port-forward $POD_NAME 8080:$CONTAINER_PORT
```

Figure 9.17 Helm install terminal output, showing the Kubernetes run commands

Copy and paste both `exports` and `kubectl` commands in the terminal from the output of the `helm install` command. Once the commands have been run, the code shown in figure 9.18 should be output to the terminal.