```
name: Run contract tests     #1

on: push     #2

env:                                                    #3
  PACT_BROKER_BASE_URL:
${{ secrets.PACT_BROKER_BASE_URL }}                    #3
  PACT_BROKER_TOKEN: ${{ secrets.PACT_BROKER_TOKEN }}    #3

jobs:
  contract-test:     #4
    runs-on: ubuntu-latest
    steps:                                          #5
      - uses: actions/checkout@v4                   #5
      - uses: actions/setup-node@v4                 #5
        with:                                       #5
          node-version: 18                          #5
      - name: Install dependencies                  #5
        run: npm i                                  #5
      - name: Run web consumer contract tests       #5
        run: npm run test:web:consumer              #5
      - name: Publish contract to PactFlow          #5
        run: npm run publish:pact                   #5
      - name: Run provider contract tests           #5
        run: npm run test:provider                  #5
```

#1 The workflow's name
#2 The event that will trigger the workflow
#3 The environment variables needed for the workflow
#4 The job's name
#5 The series of steps to run the workflow

When integrating your contract tests to a CI/CD platform, make sure that any environment variables are stored securely as a secret. In our case, we need to store the `PACT_BROKER_BASE_URL` and `PACT_BROKER_TOKEN`. To understand how secrets are stored in GitHub Actions, check out https://mng.bz/RN60.

To see the workflow in action, run the workflow in GitHub Actions. You should end up on screen similar to figure 10.2.