```
const options = {
  provider: 'MoviesAPI',
  providerBaseUrl: `http://localhost:${port}`,
  pactBrokerToken: process.env.PACT_BROKER_TOKEN,
  providerVersion: process.env.GITHUB_SHA,
  providerVersionBranch: process.env.GITHUB_BRANCH,
  publishVerificationResult: true,
  …
}

if (process.env.PACT_PAYLOAD_URL) {     #1
  console.log(`Pact payload URL specified: ${process.env.PACT_PAYLOAD_URL}`)
  options.pactUrls = [process.env.PACT_PAYLOAD_URL]
} else {     #2
  console.log(
    `Using Pact Broker Base URL:
    ${process.env.PACT_BROKER_BASE_URL}`
  )
  options.pactBrokerUrl = process.env.PACT_BROKER_BASE_URL,
  ...
};
```

#1 Sets the options.pactUrls if PACT_PAYLOAD_URL is present
#2 Sets the options.pactBrokerURL if PACT_BROKER_BASE_URL is present

10.4.4 Retries for can-i-deploy

Now that we've created a workflow that will automatically trigger the provider verification, we might end up in situations where the provider verification result is unknown because the provider build is still running and may still need to finish running before the can-i-deploy consumer job. In this situation, the result of can-i-deploy will be unknown. To address this, you can add the `--retry-while-unknown=<NUM>` as part of the can-i-deploy command, as shown in the following code snippet, where `<NUM>` corresponds to the number of times to retry the can-i-deploy tool while the provider verification is still running and the result is still unknown:

```
"scripts": {
    "can:i:deploy:consumer": "pact-broker can-i-deploy
--pacticipant WebConsumer --version=$GITHUB_SHA
--to-environment production --retry-while-unknown=10"
  }
```

10.4.5 Testing the webhook

To test the webhook, create a fork of https://github.com/mdcruz/consumer-example, and clone the project locally. Once you have a copy of the project, switch to a new branch, and update the consumer expectation of