Listing 11.1 Cypress `intercept` and `wait` commands

```
describe('Movies', () => {
    before(() => {
        cy.setupPact('BiWebConsumer', 'MoviesAPI');
        cy.intercept('http://localhost:3001/movie/1', {
            statusCode: 200,
            body: { id: 1, name: "finding nemo", year: 2003 }
        }).as('movies');
    });

    it('Movies list', () => {
        cy.visit('/');
        cy.usePactWait('movies').its('response.statusCode').should('eq', 200);
        cy.contains('finding nemo').should('be.visible');
    });
});
```

Before we run the Cypress test, we need to set up a couple of things to use the Pact command and generate the contract file. First, the `pact-cypress-adapter` package needs to be installed:

```
npm i -D @pactflow/pact-cypress-adapter
```

After installing the package, the Cypress project can use the support commands and plugin functions. Add the plugin to `setupNodeEvents` within the e2e Cypress configuration file (cypress.config.js).

Listing 11.2 Cypress plugin `config`

```
const pactCypressPlugin =
require('@pactflow/pact-cypress-adapter/dist/plugin');
const fs = require('fs');

module.exports = defineConfig({
  e2e: {
    setupNodeEvents(on, config) {
      pactCypressPlugin(on, config, fs)
      return (on, config)
    },
  },
});
```

Finally, import the Cypress Pact adapter commands within the e2e file in the support folder.

Listing 11.3 Cypress support `import`

```
import '@pactflow/pact-cypress-adapter';
```