Listing 11.5 Cypress Pact adapter contract

```
{
    "consumer": {
        "name": "BiWebConsumer"
    },
    "provider": {
        "name": "MoviesAPI"
    },
    "interactions": [
        {
            "description": "Movies list",
            "providerState": "",
            "request": {
                "method": "GET",
                "path": "/movie/1",      #1
                "headers": {
                    "accept": "*/*"
                },
                "body": "",
                "query": ""
            },
            "response": {
                "status": 200,
                "headers": {
                    "content-type": "application/json",
                    "access-control-allow-origin": "http://localhost:8000"
                },
                "body": {      #2
                    "id": 1,
                    "name": "finding nemo",
                    "year": 2003
                }
            }
        }
    ],
    "metadata": {
        "pactSpecification": {
            "version": "2.0.0"
        },
        "client": {      #3
            "name": "pact-cypress-adapter",
            "version": "1.3.0"
        }
    }
}
```

#1 Intercepted request URL path
#2 Response body expectations
#3 Pact consumer adapter reference

11.2.2 WireMock consumer adapter

In this example, we'll use WireMock to generate our contracts from mock responses. The WireMock server will return the mock responses. Then, Atlassian's WireMock Pact Generator will convert the requests and responses from the WireMock server. Add the dependencies Kotlin