WireMock and WireMock Pact Generator to the app's build Gradle file (found in the GitHub repository at consumer-mobile/app/build.gradle.kts), as follows.

Listing 11.6 Gradle build test dependencies

```
    testImplementation("com.marcinziolo:kotlin-wiremock:0.0.0")
    testImplementation("com.atlassian.ta:wiremock-pact-generator:0.0.0")
```

Before we run the JUnit test, we need to set up WireMock to listen to the requests and generate the contract file. First, the WireMock server needs to be started, as shown in listing 11.7. Within the test class, a port is found and assigned to the local URL for the WireMock server. Then, the WireMock server `start` method is called within the `BeforeEach` function. Remember to stop the WireMock server after the test finishes too.

Listing 11.7 JUnit test with WireMock

```
import com.github.tomakehurst.wiremock.WireMockServer
import com.github.tomakehurst.wiremock.common.ConsoleNotifier
import com.github.tomakehurst.wiremock.core.WireMockConfiguration.options
import java.net.ServerSocket

@TestInstance(TestInstance.Lifecycle.PER_CLASS)
class MoviesApiBiTest {
    private val port = ServerSocket(0)
      .use { socket -> return@use socket.localPort }
    private val url
        get() = "http://localhost:$port"
    private var wireMockServer: WireMockServer? =
    WireMockServer(options().port(port).notifier(ConsoleNotifier(true)))

    @BeforeEach
    fun setUp() {
        wireMockServer?.start()

    ...

    @AfterEach
    fun afterEach() {
        wireMockServer?.resetAll()
        wireMockServer?.stop()
    }
```

A request listener needs to be configured for the contract to be generated from the WireMock server, as shown in listing 11.8. The Pact generator is built with the Pact provider name set and added to the WireMock server as a listener.