Listing 11.11 WireMock generated Pact file

```
{
  "consumer": {
    "name": "BiMoviesAndroidApp"
  },
  "provider": {
    "name": "BiWiremockMoviesAPI"
  },
  "interactions": [
    {
      "description": "GET /movies -> 200",
      "request": {
        "method": "GET",
        "path": "/movies",
        "headers": {
          "connection": "keep-alive",
          "accept-encoding": "gzip",
          "user-agent": "okhttp/5.0.0-alpha.2"
        }
      },
      "response": {
        "status": 200,
        "headers": {
          "content-type": "application/json"
        },
        "body": {
          "data": [
            {
              "Id": 100,
              "Name": "Frozen",
              "Year": 2013
            }
          ]
        }
      }
    }
  ]
}
```

11.2.3 Publish consumer contracts

Creating consumer contracts from mocks generates a contract in the Pact specification format. Therefore, the generated Pact file can be published as described in chapter 4, section 4.4. For the Cypress and WireMock examples, update the folder location, if necessary, with the `publish:pact` script, as shown in the following listing.

Listing 11.12 The `publish:pact` script

```
"publish:pact": "pact-broker publish ./pacts --consumer-app-
version=1.0.0 --tag=main --broker-base-url=$PACT_BROKER_BASE_URL --broker-
token=$PACT_BROKER_TOKEN
```