Listing 12.7 E2E Cypress search result test

```
describe('GitHub website', () => {
    it('search query', () => {
        cy.visit('https://github.com/')
        cy.get('[aria-label="Search or jump to…"]').click()
        cy.get('#query-builder-test').type('pact')
        cy.get('[role="listbox"]').within(() => {
            cy.get('[data-type="url-result"]').children(() => {
                cy.get('a').should('have.attr', 'href', '/pact-foundation/pact_brok
er')
            })
        })
    })
})
```

In this example, the `href` attribute would come from the suggestion's response. The response to provide suggestions is sent to the GitHub user while searching. For the E2E test, a mock could replace the API response. The API response could be replaced within the Cypress test, and the `href` attribute could be verified within a Pact contract test, as shown in listing 12.8.

Listing 12.8 Contract Pact search result test

```
test('it should return suggested repositories', async () => {
      provider
        .uponReceiving('search suggested repositories')
        .withRequest({
          method: 'GET',
          path: '/search/suggestions',
        })
        .willRespondWith({
          headers: { 'Content-Type': 'application/json' },
          status: 200,
          body: like([{href: "pact-foundation/pact_broker"}]),
        });

      await provider.executeTest(async mockProvider => {
        const suggestions = await fetchSearchSuggestions(mockProvider.url);
        expect(suggestions).toHaveProperty('href');
      });
    });
```

The method shown in listings 12.7 and 12.8 of dividing E2E test coverage between E2E scenarios and contract tests is possible using the provider-driven contract testing (PDCT) approach demonstrated in chapter 11 as well.