```
{
    "description": "a request to all movies",
    "request": {             #1
      "method": "GET",       #1
      "path": "/movies"      #1
    },                       #1
    "response": {                              #2
      "body": [                                #2
        {                                      #2
          "id": 1,                             #2
          "name": "My movie",                  #2
          "year": 1999                         #2
        }                                      #2
      ],                                       #2
      "headers": {                             #2
        "Content-Type": "application/json"     #2
      },                                       #2
      "matchingRules": {            #3
        "body": {                   #3
          "$": {                    #3
            "combine": "AND",       #3
            "matchers": [           #3
              {                     #3
                "match": "type",    #3
                "min": 1            #3
              }                     #3
            ]                       #3
          }                         #3
        }                           #3
      },                            #3
      "status": 200    #4
    }
}
```

#1 The request from the consumer
#2 The response the consumer expects from the provider when the request is made
#3 The matching rules applied. In this example, the matching rule is that the data type of the data should match the consumer expectation. For example, the movie name should be of type string, whereas the ID and year should be of type integer.
#4 The status code the consumer expects from the provider

After the contract is generated, the consumer uploads the contract with a version to a shared broker that the provider can access. At this stage, if the test is running as part of a CI pipeline, the consumer waits for the provider to verify the contract before deploying the changes to production. This is made possible with the use of the can-i-deploy tool, which we'll talk about in more detail in chapter 10.

1.5.2 Example of a provider contract test

To verify the expectations from the consumer, a provider contract test needs to be set up. Looking at the provider/provider-contract.spec.js file of