exchanging user information with 378 – 379
role-based access control with 420 – 423
defining authorization policies based on user roles 422 – 423
extracting user roles from Access Token 421 – 422

K

k3d option 585
key/value pairs 494
key/value pairs. *See* properties
Keycloak
configuring access to user roles in 413 – 415
configuring integration between Spring Security and 383 – 384, 418 – 419, 429
configuring user logout in 390 – 393
managing user accounts with 370 – 374
defining security realm 372
managing users and roles 373 – 374
registering application in 379 – 382
running using Helm chart 597 – 599
keycloak-issuer-resourceserver-secret keycloak 530
keycloak-system namespace 598
KeyResolver bean 315
kind option to install Kubernetes 585
kind section, of Kubernates manifest 223 – 224
Knative 574 – 580
deploying applications with Knative CLI 575 – 577
deploying applications with Knative manifests 577 – 580
setting up local Knative platform 575
Knative CLI 575 – 577, 588
Knative Eventing 574
Knative in Action (Chester) 580
Knative Serving 574
Kounev R. 7
Kratzke, N. 27
kubectl api-resources command 223
kubectl apply command 220
kubectl command 227
kubectl delete deployment <name> Kubernates CLI command 586
kubectl delete -f services command 221
kubectl delete pod <name> Kubernates CLI command 587
kubectl delete svc <service> Kubernates CLI command 587
kubectl describe pod <pod_name> command 228
kubectl explain <object_name> command 223, 225
kubectl get deployment Kubernates CLI command 586
kubectl get pod Kubernates CLI command 586
kubectl get pod -l app=catalog-service 515
kubectl get svc Kubernates CLI command 586
kubectl logs <pod_id> Kubernates CLI command 586
kubectl port-forward command 235, 324, 496, 539
kubectl port-forward svc <service> <host-port> Kubernates CLI command 587
kube-proxy proxy 232