```
public class BookService {

  ...

  public Book editBookDetails(String isbn, Book book) {
    return bookRepository.findByIsbn(isbn)
      .map(existingBook -> {
        var bookToUpdate = new Book(
          existingBook.id(),                    ❶
          existingBook.isbn(),
          book.title(),
          book.author(),
          book.price(),
          existingBook.version());              ❷
        return bookRepository.save(bookToUpdate);
      })
      .orElseGet(() -> addBookToCatalog(book));
  }
}
```

❶ Uses the identifier of the existing book

❷ Uses the version of the existing book, which will be increased automatically if the update operation succeeds

In `BookDataLoader`, we can use the new static factory method for building `Book` objects. The framework will take care of handling the `id` and `version` fields.

Listing 5.6 Using the static factory method when creating a book

```
package com.polarbookshop.catalogservice.demo;

@Component
@Profile("testdata")
public class BookDataLoader {

  ...

  @EventListener(ApplicationReadyEvent.class)
  public void loadBookTestData() {
    var book1 = Book.of("1234567891", "Northern Lights",
      "Lyra Silverstar", 9.90);                 ❶
    var book2 = Book.of("1234567892", "Polar Journey",
      "Iorek Polarson", 12.90);                 ❶
    bookRepository.save(book1);
    bookRepository.save(book2);
```