Create a new application-integration.yml file in src/test/resources, and add the following configuration.

Listing 5.17 Using a PostgreSQL data source provided by Testcontainers

```
spring:
  datasource:
    url: jdbc:tc:postgresql:14.4:///      ❶
```

❶ Identifies the PostgreSQL module in Testcontainers. “14.4” is the version of PostgreSQL to use.

That’s all we need to configure Testcontainers. When the `integration` profile is enabled, Spring Boot will use the PostgreSQL container instantiated by Testcontainers. We’re now ready to write autotests to verify the data persistence layer.

5.3.2 Testing data persistence with @DataJdbcTest and Testcontainers

As you might recall from chapter 3, Spring Boot allows you to run integration tests by loading only the Spring components used by a specific application slice (*slice tests*). In Catalog Service, we created tests for the MVC and the JSON slices. Now I’ll show you how to write tests for the data slice.

Create a `BookRepositoryJdbcTests` class, and mark it with the `@DataJdbcTest` annotation. That will trigger Spring Boot to include all Spring Data JDBC entities and repositories in the application context. It will also auto-configure `JdbcAggregateTemplate`, a lower-level object we can use to set up the context for each test case instead of using the repository (the object under testing).

Listing 5.18 Integration tests for the Data JDBC slice