Next, create a src/main/resources/db/migration folder. That's where Flyway will look for SQL migrations by default. Inside the folder, create a V1__Initial_schema.sql file, which will contain the SQL statement for initializing the database schema required by the Catalog Service application. Ensure you type two underscores after the version number.

Flyway expects SQL migration files to comply with a specific naming pattern. Regular versioned migrations should follow this structure:

- *Prefix*—`V` for versioned migrations
- *Version*—Version number using dots or underscores to separate it into multiple parts (e.g., 2.0.1)
- *Separator*—Two underscores: `__`
- *Description*—Words separated by underscores
- *Suffix*—`.sql`

In the V1__Initial_schema.sql migration script, you can include the SQL instructions to create a `book` table that Spring Boot JDBC will map to the `Book` persistent entity.

Listing 5.21 Flyway migration script for schema initialization

```
CREATE TABLE book (                                          ❶
  id                 BIGSERIAL PRIMARY KEY NOT NULL,         ❷
  author             varchar(255) NOT NULL,
  isbn               varchar(255) UNIQUE NOT NULL,           ❸
  price              float8 NOT NULL,
  title              varchar(255) NOT NULL,
  created_date       timestamp NOT NULL,
  last_modified_date timestamp NOT NULL,
  version            integer NOT NULL
);
```

❶ Definition of the book table

❷ Declares the id field as the primary key