number.

❸ The JVM version to be installed in the image. It uses the latest Java 17 version.

Go ahead and build the image by running the following command:

```
$ ./gradlew bootBuildImage
```

WARNING At the time of writing, the Paketo project is working on adding support for ARM64 images. You can follow the feature's progress on the Paketo Buildpacks project on GitHub: https://github.com/paketo-buildpacks/stacks/issues/51. Until it's complete, you can still use Buildpacks to build containers and run them via Docker Desktop on Apple Silicon computers. However, the build process and the application startup phase will be slower than usual. Until official support is added, you can alternatively use the following command, pointing to an experimental version of Paketo Buildpacks with ARM64 support: `./gradlew bootBuildImage --builder ghcr.io/thomasvitale/java-builder-arm64`. Be aware that it's experimental and not ready for production. For more information, you can refer to the documentation on GitHub: https://github.com/ThomasVitale/paketo-arm64.

The first time you run the task, it will take a minute to download the packages used by Buildpacks to create the container image. The second time, it will take only a few seconds. If you look closely at the output of the command, you can see all the steps performed by Buildpacks to generate the image. These steps include adding a JRE and using the layered JAR built by Spring Boot. The plugin accepts more properties to customize its behavior, such as providing your own builder component instead of Paketo's. Check the official documentation for the complete list of configuration options (https://spring.io/projects/spring-boot).

Let's try running Catalog Service as a container once again, but this time we'll use the image generated by Buildpacks. Remember to start the PostgreSQL container first, following the instructions in section 6.2.1:

```
$ docker run -d \
    --name catalog-service \
    --net catalog-network \
    -p 9001:9001 \
    -e SPRING_DATASOURCE_URL=
```