```
    name: Package and Publish
    if: ${{ github.ref == 'refs/heads/main' }}    ❷
    needs: [ build ]                              ❸
    runs-on: ubuntu-22.04                         ❹
    permissions:
      contents: read                              ❺
      packages: write                             ❻
      security-events: write                      ❼
    steps:
      - name: Checkout source code
        uses: actions/checkout@v3                 ❽
      - name: Set up JDK
        uses: actions/setup-java@v3               ❾
        with:
          distribution: temurin
          java-version: 17
          cache: gradle
      - name: Build container image
        run: |
          chmod +x gradlew
          ./gradlew bootBuildImage \              ❿
            --imageName
            ➥ ${{ env.REGISTRY }}/${{ env.IMAGE_NAME }}:${{ env.VERSION }}
```

❶ The job's unique identifier

❷ Runs the job only on the main branch

❸ Runs the job only if the "build" job completes successfully

❹ Runs the job on an Ubuntu 22.04 machine

❺ Permission to check out the current Git repository

❻ Permission to upload images to GitHub Container Registry

❼ Permission to submit security events to GitHub

❽ Checks out the current Git repository (catalog-service)

❾ Installs and configures a Java runtime

❿ Relies on the Buildpacks integration in Spring Boot to build a container image and defines the name for the release candidate

After packaging the application as a container image, let's update the commit-stage.yml file to use grype to scan the image for vulnerabilities and publish a report to GitHub, similar to what we did in chapter 3. Finally, we can authenticate with the container registry and push the image representing our release candidate.