The `dependencies` section of the autogenerated build.gradle file is shown here:

```
dependencies {
  implementation 'org.springframework.boot:spring-boot-starter-data-r2dbc'
  implementation 'org.springframework.boot:spring-boot-starter-validation'
  implementation 'org.springframework.boot:spring-boot-starter-webflux'

  runtimeOnly 'org.postgresql:r2dbc-postgresql'

  testImplementation 'org.springframework.boot:spring-boot-starter-test'
  testImplementation 'io.projectreactor:reactor-test'
  testImplementation 'org.testcontainers:junit-jupiter'
  testImplementation 'org.testcontainers:postgresql'
  testImplementation 'org.testcontainers:r2dbc'
}
```

These are the main dependencies:

- *Spring Reactive Web* (`org.springframework.boot:spring-boot-starter-webflux`)—Provides the necessary libraries for building reactive web applications with Spring WebFlux and includes Netty as the default embedded server.
- *Spring Data R2DBC* (`org.springframework.boot:spring-boot-starter-data-r2dbc`)—Provides the necessary libraries to persist data in relational databases with R2DBC using Spring Data in reactive applications.
- *Validation* (`org.springframework.boot:spring-boot-starter-validation`)—Provides the necessary libraries for object validation using the Java Bean Validation API.