Then you can write the SQL script for creating the `orders` table in a V1__Initial_ schema.sql file under src/main/resources/db/migration. Ensure you type two underscores after the version number.

Listing 8.10 Flyway migration script for schema initialization

```
CREATE TABLE orders (                                    ❶
  id                 BIGSERIAL PRIMARY KEY NOT NULL,     ❷
  book_isbn          varchar(255) NOT NULL,
  book_name          varchar(255),
  book_price         float8,
  quantity           int NOT NULL,
  status             varchar(255) NOT NULL,
  created_date       timestamp NOT NULL,
  last_modified_date timestamp NOT NULL,
  version            integer NOT NULL
);
```

❶ Definition of the orders table

❷ Declares the id field as the primary key

Finally, open the application.yml file, and configure Flyway to use the same database managed with Spring Data R2DBC but using the JDBC driver.

Listing 8.11 Configuring the Flyway integration over JDBC

```
spring:
  r2dbc:
    username: user
    password: password
    url: r2dbc:postgresql://localhost:5432/polardb_order
    pool:
      max-create-connection-time: 2s
      initial-size: 5
      max-size: 10
  flyway:
    user: ${spring.r2dbc.username}                       ❶
    password: ${spring.r2dbc.password}                   ❷
    url: jdbc:postgresql://localhost:5432/polardb_order  ❸
```

❶ Gets the value from the username configured for R2DBC

❷ Gets the value from the password configured for R2DBC