❷ The property for specifying the Catalog Service URI. It cannot be null.

NOTE To get autocompletion and type-validation checks from your IDE, you need to add a dependency on `org.springframework.boot:spring-boot-configuration-processor` with scope `annotationProcessor` in the build .gradle file, like you did in chapter 4. You can refer to the Chapter08/08-end/order-service/build.gradle file in the code repository accompanying the book to check the final result (https://github.com/ThomasVitale/cloud-native - spring-in-action).

Then, enable the custom configuration properties in your `OrderServiceApplication` class using the `@ConfigurationPropertiesScan` annotation.

Listing 8.17 Enabling custom configuration properties

```
package com.polarbookshop.orderservice;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.boot.context.properties
➥ .ConfigurationPropertiesScan;

@SpringBootApplication
@ConfigurationPropertiesScan                    ❶
public class OrderServiceApplication {
  public static void main(String[] args) {
    SpringApplication.run(OrderServiceApplication.class, args);
  }
}
```

❶ Loads configuration data beans in the Spring context

Finally, add a value for the new property to your application.yml file. As a default, you can use the URI for the Catalog Service instance running in your local environment.

Listing 8.18 Configuring the URI for Catalog Service (application.yml)

```
...
polar:
  catalog-service-uri: "http://localhost:9001"
```