where you are going to use the `WebClient` bean to send HTTP calls to the `GET /books/{bookIsbn}` endpoint exposed by Catalog Service through its fluent API. The `WebClient` will ultimately return a `Book` object wrapped in a `Mono` publisher.

Listing 8.21 Defining a reactive REST client using `WebClient`

```
package com.polarbookshop.orderservice.book;

import reactor.core.publisher.Mono;
import org.springframework.stereotype.Component;
import org.springframework.web.reactive.function.client.WebClient;

@Component
public class BookClient {
  private static final String BOOKS_ROOT_API = "/books/";
  private final WebClient webClient;

  public BookClient(WebClient webClient) {
    this.webClient = webClient;                    ❶
  }

  public Mono<Book> getBookByIsbn(String isbn) {
    return webClient
      .get()                                       ❷
      .uri(BOOKS_ROOT_API + isbn)                  ❸
      .retrieve()                                  ❹
      .bodyToMono(Book.class);                     ❺
  }
}
```

❶ A WebClient bean as configured previously

❷ The request should use the GET method.

❸ The target URI of the request is /books/{isbn}.

❹ Sends the request and retrieves the response

❺ Returns the retrieved object as Mono<Book>

`WebClient` is a reactive HTTP client. You've just seen how it can return data as reactive publishers. In particular, the result of calling Catalog Service to fetch details about a specific book is a `Mono<Book>` object. Let's see