A *namespace* is “an abstraction used by Kubernetes to support isolation of groups of resources within a single cluster. Namespaces are used to organize objects in a cluster and provide a way to divide cluster resources” (https://kubernetes.io/docs/reference/glossary).

We use namespaces to keep our clusters organized and define network policies to keep certain resources isolated for security reasons. So far, we’ve been working with the `default` namespace, and we’ll keep doing that for all our Polar Bookshop applications. However, when it comes to platform services such as Ingress NGINX, we’ll rely on dedicated namespaces to keep those resources isolated.

Now that Ingress NGINX is installed, let’s go ahead and deploy the backing services used by our Polar Bookshop applications. Check the source code repository accompanying this book (Chapter09/09-end) and copy the content of the polar-deployment/kubernetes/platform/development folder into the same path in your `polar-deployment` repository, overwriting any existing file we used in previous chapters. The folder contains basic Kubernetes manifests to run PostgreSQL and Redis.

Open a Terminal window, navigate to the kubernetes/platform/development folder located in your `polar-deployment` repository, and run the following command to deploy PostgreSQL and Redis in your local cluster:

```
$ kubectl apply -f services
```

You can verify the results with the following command:

```
$ kubectl get deployment
NAME             READY   UP-TO-DATE   AVAILABLE   AGE
polar-postgres   1/1     1            1           73s
polar-redis      1/1     1            1           73s
```