1. In the `SecurityConfig` class, define an `oidcLogoutSuccessHandler()` method to build an `OidcClientInitiatedServerLogoutSuccessHandler` object.
2. Configure the post-logout redirect URL using the `setPostLogoutRedirectUri()` method.
3. Call the `oidcLogoutSuccessHandler()` method from the `logout()` configuration defined in the `SecurityWebFilterChain` bean.

The resulting configuration in the `SecurityConfig` class is as follows.

Listing 11.11 Configuring RP-Initiated Logout and redirecting on logout

```
package com.polarbookshop.edgeservice.config;

import org.springframework.context.annotation.Bean;
import org.springframework.security.config.Customizer;
import org.springframework.security.config.annotation.web.reactive.
➥ EnableWebFluxSecurity;
import org.springframework.security.config.web.server.ServerHttpSecurity;
import org.springframework.security.oauth2.client.oidc.web.server.logout.
➥ OidcClientInitiatedServerLogoutSuccessHandler;
import org.springframework.security.oauth2.client.registration.
➥ ReactiveClientRegistrationRepository;
import org.springframework.security.web.server.SecurityWebFilterChain;
import org.springframework.security.web.server.authentication.logout.
➥ ServerLogoutSuccessHandler;

@EnableWebFluxSecurity
public class SecurityConfig {

  @Bean
  SecurityWebFilterChain springSecurityFilterChain(
    ServerHttpSecurity http,
    ReactiveClientRegistrationRepository clientRegistrationRepository
  ) {
    return http
      .authorizeExchange(exchange ->
        exchange.anyExchange().authenticated())
```