Listing 12.6 Adding dependency for Spring Security OAuth2 Resource Server

```
dependencies {
  ...
  implementation 'org.springframework.boot:
  ➥ spring-boot-starter-oauth2-resource-server'
}
```

Next, let's configure the integration between Spring Security and Keycloak.

CONFIGURING THE INTEGRATION BETWEEN SPRING SECURITY AND KEYCLOAK

Spring Security supports protecting endpoints using two data formats for the Access Token: JWT and opaque tokens. We'll work with Access Tokens defined as JWTs, similar to what we did for ID Tokens. With Access Tokens, Keycloak grants Edge Service access to downstream applications on behalf of the user. When the Access Token is a JWT, we can also include relevant information as claims about the authenticated user and propagate this context to Catalog Service and Order Service with ease. In contrast, opaque tokens would require the application downstream to contact Keycloak every time to fetch the information associated with the token.

Configuring Spring Security to integrate with Keycloak as an OAuth2 Resource Server is more straightforward than the OAuth2 Client scenario. When working with JWTs, the application will contact Keycloak mainly to fetch the public keys necessary to verify the token's signature. Using the `issuer-uri` property, similar to what we did for Edge Service, we'll let the application auto-discover the Keycloak endpoint where it can find the public keys.