DEFINING AN AUDITOR TO CAPTURE WHO CREATED OR UPDATED A JDBC DATA ENTITY

In the Catalog Service project (catalog-service), open the `DataConfig` class. That's where we used the `@EnableJdbcAuditing` annotation to enable data auditing. Now, we'll also define an `AuditorAware` bean that should return the principal—the currently authenticated user.

Listing 12.21 Configuring user auditing in Spring Data JDBC

```
@Configuration
@EnableJdbcAuditing                                    ❶
public class DataConfig {

  @Bean
  AuditorAware<String> auditorAware() {                ❷
    return () -> Optional
      .ofNullable(SecurityContextHolder.getContext())  ❸
      .map(SecurityContext::getAuthentication)         ❹
      .filter(Authentication::isAuthenticated)         ❺
      .map(Authentication::getName);                   ❻
  }
}
```

❶ Enables entity auditing in Spring Data JDBC

❷ Returns the currently authenticated user for auditing purposes

❸ Extracts the SecurityContext object for the currently authenticated user from SecurityContextHolder

❹ Extracts the Authentication object for the currently authenticated user from SecurityContext

❺ Handles the case where a user is not authenticated, but is manipulating data. Since we protected all the endpoints, this case should never happen, but we'll include it for completeness.

❻ Extracts the username for the currently authenticated user from the Authentication object

ADDING AUDIT METADATA FOR USERS WHO CREATED OR UPDATED A JDBC DATA ENTITY