time we'll get the `SecurityContext` object for the principal from the `ReactiveSecurityContextHolder`.

In the Order Service project (order-service), open the `DataConfig` class and add a `ReactiveAuditorAware` bean to return the username of the currently authenticated user.

Listing 12.26 Configuring user auditing in Spring Data R2DBC

```
@Configuration
@EnableR2dbcAuditing                                    ❶
public class DataConfig {

  @Bean
  ReactiveAuditorAware<String> auditorAware() {         ❷
    return () ->
      ReactiveSecurityContextHolder.getContext()        ❸
        .map(SecurityContext::getAuthentication)        ❹
        .filter(Authentication::isAuthenticated)        ❺
        .map(Authentication::getName);                  ❻
  }
}
```

❶ Enables entity auditing in Spring Data R2DBC

❷ Returns the currently authenticated user for auditing purposes

❸ Extracts the SecurityContext object for the currently authenticated user from ReactiveSecurityContextHolder

❹ Extracts the Authentication object for the currently authenticated user from SecurityContext

❺ Handles the case where a user is not authenticated, but it is manipulating data. Since we protected all the endpoints, this case should never happen, but we'll include it for completeness.

❻ Extracts the username of the currently authenticated user from the Authentication object

ADDING AUDIT METADATA FOR USERS WHO CREATED OR UPDATED AN R2DBC DATA ENTITY