❹ Volumes are used to load configuration for collecting and delivering logs.

Next, start all three containers with the following command:

```
$ docker-compose up -d grafana
```

Thanks to the dependencies defined in Docker Compose between containers, starting Grafana will also run Loki and Fluent Bit.

Fluent Bit can be configured to collect logs from different sources. For Polar Bookshop we'll rely on the Fluentd driver available in Docker to collect logs automatically from running containers. The Docker platform itself listens to the log events from each container and routes them to the specified service. In Docker, a logging driver can be configured directly on a container. For example, update the Catalog Service configuration in Docker Compose to use the Fluentd logging driver, which will send the logs over to the Fluent Bit container.

Listing 13.4 Using Fluentd driver to route container logs to Fluent Bit

```
version: "3.8"
services:
  ...

  catalog-service:
    depends_on:
      - fluent-bit                                          ❶
      - polar-keycloak
      - polar-postgres
    image: "catalog-service"
    container_name: "catalog-service"
    ports:
      - 9001:9001
      - 8001:8001
    environment:
      - BPL_JVM_THREAD_COUNT=50
      - BPL_DEBUG_ENABLED=true
      - BPL_DEBUG_PORT=8001
      - SPRING_CLOUD_CONFIG_URI=http://config-service:8888
      - SPRING_DATASOURCE_URL=
➥jdbc:postgresql://polar-postgres:5432/polardb_catalog
```