```
  ...

  catalog-service:
    depends_on:
      - fluent-bit
      - polar-keycloak
      - polar-postgres
      - tempo                                                    ❶
    image: "catalog-service"
    container_name: "catalog-service"
    ports:
      - 9001:9001
      - 8001:8001
    environment:
      - JAVA_TOOL_OPTIONS=-javaagent:/workspace/BOOT-INF/lib/
      ➥ opentelemetry-javaagent-1.17.0.jar                      ❷
      - OTEL_SERVICE_NAME=catalog-service                        ❸
      - OTEL_EXPORTER_OTLP_ENDPOINT=http://tempo:4317            ❹
      - OTEL_METRICS_EXPORTER=none
    ...
```

❶ Ensures Tempo is started before Catalog Service

❷ Instructs the JVM to run the OpenTelemetry Java agent from the path where Cloud Native Buildpacks placed the application dependencies

❸ The name of the application, used to tag the traces produced by Catalog Service

❹ The URL of the distributed tracing backend supporting the OpenTelemetry protocol (OTLP)

Finally, from the same folder, run Catalog Service as a container:

```
$ docker-compose up -d catalog-service
```

Once the application is up and running, send a few requests to trigger the generation of some logs and traces about your HTTP requests:

```
$ http :9001/books
```

Then check the logs from the container (`docker logs catalog-service`). You'll see that each log message now has a new section containing the application name and, when available, the trace and span identifiers: