```
- behavior: merge                  ❶
  files:
    - application-staging.yml     ❷
  name: catalog-config            ❸
```

❶ Merges this ConfigMap with the one defined in the base Kustomization

❷ The additional property file added to the ConfigMap

❸ The same ConfigMap name used in the base Kustomization

That's it for ConfigMaps. The following section will cover how you can configure which image name and version to deploy.

14.3.6 Customizing image name and version

The base Deployment manifest defined in the Catalog Service repository (catalog-service/k8s/deployment.yml) is configured to use a local container image and doesn't specify a version number (which means the `latest` tag is used). That's convenient in the development phase, but it doesn't work for other deployment environments.

If you followed along, you should have your Catalog Service source code tracked in a `catalog-service` repository on GitHub and a `ghcr.io/<your_github_username>/catalog-service:latest` container image published to GitHub Container Registry (as per the Commit Stage workflow). The next chapter will cover release strategies and versioning. Until then, we'll still use the `latest` tag. Regarding the image name, though, it's time to start pulling container images from the registry rather than using the local ones.

NOTE Images published to GitHub Container Registry will have the same visibility as the related GitHub code repository. I'll assume that all the images we build for Polar Bookshop are publicly accessible via the GitHub Container Registry. If that's not the case, you can go to the specific repository page on GitHub and access the Packages section for that repository. Then select Package