Settings from the sidebar menu, scroll to the bottom of the settings page, and make the package public by clicking the Change Visibility button.

Similar to what we've done for environment variables, we could use a patch to change the image that's used by the Catalog Service Deployment resource. Since it's a very common customization and would need to be changed every time we deliver a new version of our applications, however, Kustomize provides a more convenient way to declare which image name and version we want to use for each container. Furthermore, we can either update the kustomization.yml file directly or rely on the Kustomize CLI (installed as part of the Kubernetes CLI). Let's try the latter.

Open a Terminal window, navigate to the staging overlay for Catalog Service (kubernetes/applications/catalog-service/staging), and run the following command to define which image and version to use for the `catalog-service` container. Remember to replace `<your_github_username>` with your GitHub username in lowercase:

```
$ kustomize edit set image \
    catalog-service=ghcr.io/<your_github_username>/catalog-service:latest
```

This command will automatically update the kustomization.yml file with the new configuration, as you can see in the following listing.

Listing 14.15 Configuring the image name and version for the container

```
apiVersion: kustomize.config.k8s.io/v1beta1
kind: Kustomization

resources:
  - github.com/<your_github_username>/catalog-service/k8s?ref=main

patchesStrategicMerge:
  - patch-env.yml

configMapGenerator:
```