In this section, you'll see how to implement the skeleton of a workflow for the acceptance stage using GitHub Actions. Throughout the book we've focused on unit and integration tests, which we run in the commit stage. For the acceptance stage, we would need to write functional and non-functional acceptance tests. That's out of scope for this book, but I still want to show you some principles for designing the workflow using Catalog Service as an example.

Open your Catalog Service project (catalog-service), and create a new acceptance-stage.yml file within the .github/workflows folder. The acceptance stage is triggered whenever a new release candidate is published to the artifact repository. One option for defining such a trigger is listening for the events published by GitHub whenever the commit stage workflow has completed a run.

Listing 15.2 Triggering the acceptance stage after the commit stage is done

```
name: Acceptance Stage                ❶
on:
  workflow_run:                       ❷
    workflows: ['Commit Stage']
    types: [completed]
    branches: main                    ❸
```

❶ The name of the workflow

❷ This workflow is triggered when the Commit Stage workflow completes a run.

❸ This workflow runs only on the main branch.

However, that's not enough. Following the continuous integration principles, developers commit often during the day and repeatedly trigger the commit stage. Since the commit stage is much faster than the acceptance stage, we risk creating a bottleneck. When an acceptance stage run has completed, we are not interested in verifying all the release candidates that have queued up