replace `<your_github_username>` with your GitHub username in lowercase. Also, replace `<release_sha>` with the unique identifier associated with your latest release candidate for Catalog Service. You can retrieve that version from the Packages section of your `catalog-service` GitHub repository main page.

Listing 15.5 Defining an overlay for production on top of a remote base

```
apiVersion: kustomize.config.k8s.io/v1beta1
kind: Kustomization

resources:                                                                    ❶
  - github.com/<your_github_username>/catalog-service/k8s?ref=<release_sha>
```

❶ The git commit hash (sha) identifying your latest release candidate

NOTE I'll assume that all the GitHub repositories you created for Polar Bookshop are publicly accessible. If that's not the case, you can go to the specific repository page on GitHub and access the Settings section for that repository. Scroll to the bottom of the settings page, and make the package public by clicking the Change Visibility button.

CUSTOMIZING ENVIRONMENT VARIABLES

The first customization we'll apply is an environment variable to activate the `prod` Spring profile for Catalog Service. Following the same approach as in the previous chapter, create a patch-env.yml file within the production overlay for Catalog Service (kubernetes/applications/catalog-service/production).

Listing 15.6 A patch for customizing environment variables in a container

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: catalog-service
spec:
```