When you set up the production environment on DigitalOcean earlier, you also created a Secret with the credentials to access the PostgreSQL database (`polar-postgres-catalog-credentials`) and another for Keycloak (`keycloak-issuer-resourceserver-secret`). Now we can mount them as volumes to the Catalog Service container, similar to what we did with ConfigMaps in chapter 14. We'll do that in a dedicated patch.

Create a patch-volumes.yml file within the production overlay for Catalog Service (kubernetes/applications/catalog-service/production), and configure the patch as shown in listing 15.8. When Kustomize applies this patch to the base deployment manifests, it will merge the ConfigMap volume defined in the base with the Secret volumes defined in the patch.

Listing 15.8 Mounting Secrets as volumes to the Catalog Service container

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: catalog-service
spec:
  template:
    spec:
      containers:
        - name: catalog-service
          volumeMounts:
            - name: postgres-credentials-volume
              mountPath: /workspace/secrets/postgres              ❶
            - name: keycloak-issuer-resourceserver-secret-volume
              mountPath: /workspace/secrets/keycloak              ❷
      volumes:
        - name: postgres-credentials-volume
          secret:                                                 ❸
            secretName: polar-postgres-catalog-credentials
        - name: keycloak-issuer-resourceserver-secret-volume
          secret:                                                 ❹
            secretName: keycloak-issuer-resourceserver-secret
```

❶ Mounts the volume with the Secret containing the PostgreSQL credentials