❷ Mounts the volume with the Secret containing the Keycloak issuer URL

❸ Defines a volume from the Secret containing the PostgreSQL credentials

❹ Defines a volume from the Secret containing the Keycloak issuer URL

Then, just like you learned in the previous section, we need to reference the patch in the kustomization.yml file for the production overlay.

Listing 15.9 Getting Kustomize to apply the patch for mounting Secrets

```
apiVersion: kustomize.config.k8s.io/v1beta1
kind: Kustomization

resources:
  - github.com/<your_github_username>/catalog-service/k8s?ref=<release_sha>

patchesStrategicMerge:
  - patch-env.yml
  - patch-volumes.yml      ❶
```

❶ Defines a patch for mounting Secrets as volumes

Currently, the Secrets are configured to be provided to the container, but Spring Boot is not aware of them yet. In the next section I'll show you how to instruct Spring Boot to load those Secrets as config trees.

CUSTOMIZING CONFIGMAPS

The base `Kustomization` for Catalog Service instructs Kustomize to generate a `catalog-config` ConfigMap starting with an application.yml file. As you learned in the previous chapter, we can ask Kustomize to add an additional file to that same ConfigMap, application-prod.yml, which we know takes precedence over the base application.yml file. That's how we're going to customize the application configuration for production.