version. That will be the trigger for the production stage, which we'll implement in a moment.

Listing 15.17 Triggering the production stage in the deployment repository

```
name: Acceptance Stage
on:
  workflow_run:
    workflows: ['Commit Stage']
    types: [completed]
    branches: main
concurrency: acceptance

env:                                                                    ❶
  OWNER: <your_github_username>
  REGISTRY: ghcr.io
  APP_REPO: catalog-service
  DEPLOY_REPO: polar-deployment
  VERSION: ${{ github.sha }}

jobs:
  functional:
    ...
  performance:
    ...
  security:
    ...
  deliver:
    name: Deliver release candidate to production
    needs: [ functional, performance, security ]                        ❷
    runs-on: ubuntu-22.04
    steps:
      - name: Deliver application to production
        uses: peter-evans/repository-dispatch@v2                        ❸
        with:
          token: ${{ secrets.DISPATCH_TOKEN }}                          ❹
          repository:
          ➥ ${{ env.OWNER }}/${{ env.DEPLOY_REPO }}                    ❺
          event-type: app_delivery                                      ❻
          client-payload: '{                                            ❼
            "app_image":
              "${{ env.REGISTRY }}/${{ env.OWNER }}/${{ env.APP_REPO }}",
            "app_name": "${{ env.APP_REPO }}",
            "app_version": "${{ env.VERSION }}"
          }'
```

❶ Defines relevant data as environment variables