1. Check out the `polar-deployment` source code.
2. Update the production `Kustomization` with the new version for the given application.
3. Commit the changes to the `polar-deployment` repository.

We can implement those three steps as follows.

Listing 15.18 Updating the image version upon a new application delivery

```
name: Production Stage

on:
  repository_dispatch:                                              ❶
    types: [app_delivery]

jobs:
  update:
    name: Update application version
    runs-on: ubuntu-22.04
    permissions:
      contents: write
    env:                                                            ❷
      APP_IMAGE: ${{ github.event.client_payload.app_image }}
      APP_NAME: ${{ github.event.client_payload.app_name }}
      APP_VERSION: ${{ github.event.client_payload.app_version }}
    steps:
      - name: Checkout source code
        uses: actions/checkout@v3                                   ❸
      - name: Update image version
        run: |
          cd \                                                      ❹
            kubernetes/applications/${{ env.APP_NAME }}/production
          kustomize edit set image \                                ❺
            ${{ env.APP_NAME }}=${{ env.APP_IMAGE }}:${{ env.APP_VERSION }}
          sed -i 's/ref=[\w+]/${{ env.APP_VERSION }}/' \
            kustomization.yml                                       ❻
      - name: Commit updated manifests
        uses: stefanzweifel/git-auto-commit-action@v4               ❼
        with:                                                       ❽
          commit_message: "Update ${{ env.APP_NAME }}
```