```
$ argocd app create catalog-service \                                    ❶
  --repo \                                                               ❷
    https://github.com/<your_github_username>/polar-deployment.git \
  --path kubernetes/applications/catalog-service/production \            ❸
  --dest-server https://kubernetes.default.svc \                         ❹
  --dest-namespace default \                                             ❺
  --sync-policy auto \                                                   ❻
  --auto-prune                                                           ❼
```

❶ Creates a catalog-service application in Argo CD

❷ The Git repository to monitor for changes. Insert your GitHub username.

❸ The folder to monitor for changes within the configured repository

❹ The Kubernetes cluster where the application should be deployed. We are using the default cluster configured in the kubectl context.

❺ The namespace where the application should be deployed. We are using the “default” namespace.

❻ Configures Argo CD to automatically reconcile the desired state in the Git repo with the actual state in the cluster

❼ Configures Argo CD to delete old resources after a synchronization automatically

You can verify the status of the continuous deployment of Catalog Service with the following command (I have filtered the results for the sake of clarity):

```
$ argocd app get catalog-service

GROUP  KIND        NAMESPACE  NAME                        STATUS  HEALTH
       ConfigMap   default    catalog-config-6d5dkt7577  Synced
       Service     default    catalog-service            Synced  Healthy
apps   Deployment  default    catalog-service            Synced  Healthy
```

Argo CD has automatically applied the production overlay for Catalog Service (polar-deployment/kubernetes/applications/catalog-service/production) to the cluster.

Once all the resources listed by the previous command have the `Synced` status, we can verify that the application is running correctly. The application is not exposed outside the cluster yet, but you can use the port-