Figure 16.1 The parameters for initializing the Quote Service project

The project contains the following main dependencies:

- *Spring Reactive Web* provides the necessary libraries for building reactive web applications with Spring WebFlux, and it includes Netty as the default embedded server.
- *Spring Native* supports compiling Spring applications to native executables using the GraalVM native-image compiler.

The resulting `dependencies` section of the build.gradle file is as follows:

```
dependencies {
  implementation 'org.springframework.boot:spring-boot-starter-webflux'
  testImplementation 'org.springframework.boot:spring-boot-starter-test'
  testImplementation 'io.projectreactor:reactor-test'
}
```

At this point, you might ask: where is the Spring Native dependency? There isn't one. Where is Spring Native? The answer can be found in the `plugins` sections of the build.gradle file:

```
plugins {
   id 'org.springframework.boot' version '2.7.3'
   id 'io.spring.dependency-management' version '1.0.13.RELEASE'
   id 'java'
   id 'org.springframework.experimental.aot' version '0.12.1'     ❶
}
```

❶ Spring AOT plugin provided by Spring Native

When you add Spring Native to a project, you'll get the Spring AOT plugin, which provides the required configuration for GraalVM to compile the Spring classes as well as convenient functionality for building native executables from Gradle (or Maven).