The project contains the following dependencies:

- *Spring Reactive Web* provides the necessary libraries for building reactive web applications with Spring WebFlux, and it includes Netty as the default embedded server.
- *Spring Cloud Function* provides the necessary libraries to support business logic implementation via functions, export them via several communication channels, and integrate them with serverless platforms.
- *Spring Native* supports compiling Spring applications to native executables using the GraalVM native-image compiler.

The resulting dependencies section of the build.gradle file looks like the following.

```
dependencies {
  implementation 'org.springframework.boot:spring-boot-starter-webflux'
  implementation
➥'org.springframework.cloud:spring-cloud-starter-function-web'
  testImplementation 'org.springframework.boot:spring-boot-starter-test'
  testImplementation 'io.projectreactor:reactor-test'
}
```

Then you can update the Cloud Native Buildpacks configuration in build.gradle much like we did for Quote Service.

Listing 16.8 Configuration for containerizing Quote Function

```
tasks.named('bootBuildImage') {
  builder = 'paketobuildpacks/builder:tiny'      ❶
  environment = ['BP_NATIVE_IMAGE': 'true']      ❷
  imageName = "${project.name}"

  docker {
   publishRegistry {
     username = project.findProperty("registryUsername")
     password = project.findProperty("registryToken")
     url = project.findProperty("registryUrl")
```