```
  0.045s The Route is still working to reflect the latest desired
  ➥specification.
  0.096s Configuration "quote-function" is waiting for a Revision
  ➥to become ready.
  3.337s ...
  3.377s Ingress has not yet been reconciled.
  3.480s Waiting for load balancer to be ready
  3.660s Ready to serve.

Service 'quote-function' created to latest revision 'quote-function-00001'
➥is available at URL:
http://quote-function.default.127.0.0.1.sslip.io
```

Let's test it out! First we need to open a tunnel to the cluster with minikube. The first time you run this command, you might be asked to input your machine password to authorize the tunneling to the cluster:

```
$ minikube tunnel --profile knative
```

Then open a new Terminal window and call the application at the root endpoint to fetch the complete list of quotes. The URL to call is the same one returned by the previous command (`http://quote-function.default.127.0.0.1.sslip.io`), which is in the format `<service-name>.<namespace>.<domain>`:

```
$ http http://quote-function.default.127.0.0.1.sslip.io
```

Since we are working locally, I configured Knative to use sslip.io, a DNS service that "when queried with a hostname with an embedded IP address, returns that IP address." For example, the `127.0.0.1.sslip.io` hostname would be resolved to the `127.0.0.1` IP address. Since we opened a tunnel to the cluster, requests to `127.0.0.1` will be handled by the cluster, where Knative will route them to the right service.