```
- "9292:9292"
- "13133"
depends_on:
- prometheus
- jaeger
```

9292 is where we expose the Prometheus exporter.

13133 is the port used for collector health checks.

Listing 4.7 shows Prometheus configured as a metrics backend destination to land metrics that we then can query via CLI or using the built-in UI. Note that the Prometheus scrape configuration (prom-config.yaml) referenced here is something we will be discussing a bit later in the chapter (see listing 4.12).

Listing 4.7 Docker Compose configuration snippet for backend Prometheus

```
prometheus:
    image: prom/prometheus:latest
    ports:
    - "9090:9090"
    volumes:
    - ./prom-config.yaml:/etc/prometheus/prometheus.yml
```

The Prometheus config to scrape the OpenTelemetry collector

Last but not least, listing 4.8 shows how we configure Jaeger, the trace's backend destination. Here the two things to note are port 14250, which we will use in the OpenTelemetry collector as the target to send traces to, as well as the environment variable `COLLECTOR_OTLP_ENABLED`, which we (at the time of writing, for the version of Jaeger we're using here) still need to set so that the OTLP over gRPC connection between the collector and Jaeger works.

Listing 4.8 Docker Compose configuration snippet for backend Jaeger

```
jaeger:
    image: jaegertracing/all-in-one:1.36
    ports:
    - "5778:5778"
    - "14250:14250"
    - "16686:16686"
    environment:
    - "COLLECTOR_OTLP_ENABLED=true"
```

5778 is Jaeger's config interface port.

16686 is the port where Jaeger exposes its frontend UI.

14250 is the port where Jaeger receives model.proto, which is OTLP over gRPC.

Now that we know all the components of our setup, let's move on to the configuration of the OpenTelemetry collector and Prometheus. To collect metrics and traces from the sample app, we will configure the OpenTelemetry collector with two pipelines, one for metrics and one for traces, as show in listings 4.9 through 4.11 (splitting the config into receivers, exporters, and the actual services configuration), which you can find in the ch04/otel/otel-config.yaml file.

Let's begin with the ingress path, the receivers.