```
    restart: always
    command:
      - filesystem
      - --prometheus-url=http://prometheus:9090
    volumes:
      - ./pyrra:/etc/pyrra
      - ./prometheus_pyrra:/etc/prometheus/pyrra
```

The following listing shows the Prometheus config (prometheus/prometheus.yaml).

Listing 10.2 Prometheus config

```
global:
  scrape_interval: 5s
  scrape_timeout: 3s
  evaluation_interval: 5s

rule_files:
  - 'pyrra/*.yaml'

scrape_configs:
- job_name: prometheus
  static_configs:
  - targets:
    - localhost:9090
- job_name: svc
  static_configs:
  - targets:
    - svc:8765
```

Configures where Prometheus reads the rules Pyrra generated

Defines scrape jobs, Prometheus self-scraping, and our ho11y service

The next listing is the content of the YAML file pyrra/ho11y-http.yaml with the SLO definition of our `ho11y` service. We set the target to 75% overall.

Listing 10.3 Pyrra SLO definition

```
apiVersion: pyrra.dev/v1alpha1
kind: ServiceLevelObjective
metadata:
  name: ho11y-api-query
  namespace: monitoring
  labels:
    prometheus: k8s
    role: alert-rules
spec:
  target: '75.0'
  window: 7d
  indicator:
    ratio:
      errors:
        metric: ho11y_total{job="svc",http_status_code=~"4.."}
      total:
        metric: ho11y_total{job="svc"}
```

The name of the SLO

Our target value, which is 75% availability. Note that it's a string because kubebuilder doesn't support the float64 type

Defines error SLI—what we mean by errors (not available)

Overall SLI