Now, to pull in the `echo` service dependencies, run the following command:

```
$ go mod vendor
```

Complete the build by executing `go build`, as explained in listing 2.2.

2.3.2 Telemetry

We are now in the position to execute the `echo` service locally and send the log events it emits during its execution to certain destinations, such as to the screen and into a file:

```
$ ./echosvc 2>&1 | \
  tee echo.log
```

Execute the echosvc and redirect its stderr output to stdout.

Use the tee command to show the log lines on the terminal, at the same time appending the log lines to a file called echo.log. We will use this file as an input to ship to a destination in the next step.

Next, we will use some open source tools, provided by Grafana Labs, to route and collect the logs. We capture the logs of our `echo` service with Promtail (http://mng.bz/V1J0) and ship them to Loki (https://grafana.com/docs/loki/latest/) as a destination (as a data source in Grafana). Using Grafana as the frontend, you can then view and query the logs as you desire.

To set up our log scenario, use the Docker Compose manifest file shown in the following listing. It launches everything needed, from the destination to the frontend.

Listing 2.5 Using docker-compose.yaml to stand up Promtail, Loki, and Grafana

```
version: "3.5"
networks:
  loki:
services:
  loki:
    image: grafana/loki:2.4.0
    ports:
      - "3100:3100"
    command: -config.file=/etc/loki/local-config.yaml
    networks:
      - loki
  promtail:
    image: grafana/promtail:2.4.0
    volumes:
      - ./promtail-config.yaml:/etc/promtail/config.yml
      - ./echo.log:/var/log/echo.log
    command: -config.file=/etc/promtail/config.yml
    networks:
      - loki
  grafana:
    image: grafana/grafana:latest
    ports:
      - "3000:3000"
    networks:
      - loki
```

Defines the location of the Promtail config file. We map the host local file promtail-config.yaml into the container to /etc/promtail/config.yml, where Promtail expects to find it.

Maps the host local file echo.log (which our echo services logs to) into the container to /var/log/echo.log. We will use that in listing 2.6 to define the log processing and routing pipeline.