TIP While using Docker Compose to develop locally or test apps is certainly handy, for a production setup, Kubernetes is much more useful. For example, you can install the Promtail, Loki, and Grafana stack via Helm charts or using Tanka (https://tanka.dev/).

Now that we have set up the framework for launching the logs destination (Loki), the telemetry agent (Promtail), and the frontend (Grafana) via our Docker Compose file (listing 2.5) we need one more thing in place: configuring Promtail, our log router/ingester. The Docker Compose manifest references (in line 15) this Promtail configuration file, which we call promtail-config.yaml, as shown in the following listing.

Listing 2.6 Promtail configuration file promtail-config.yaml

```
server:
  http_listen_port: 9080
  grpc_listen_port: 0

positions:
  filename: /tmp/positions.yaml

clients:
  - url: http://loki:3100/loki/api/v1/push

scrape_configs:
- job_name: app
  static_configs:
  - targets:
      - localhost
    labels:
      job: echosvc
      __path__: /var/log/echo.log
 pipeline_stages:
  - json:
     expressions:
        level: level
        payload: msg
        timestamp: time
        service: service
  - labels:
     level:
      service:
```

This defines the input for Promtail. Here, we tell it to ingest logs from a file called /var/log/echo.log (which we mounted from the host via a volume in line 16 of the Docker Compose manifest).

This is the first part of the Promtail pipeline (http://mng.bz/x48e). It maps the input JSON fields that our echo service emits (e.g., service or level, the right-hand side here, the values) to labels we want to filter for in Loki; for example, service or level (the same names here, but you can, and often must, normalize keys, and that's a good place to do this).

Here, we define the labels we want to index or expose.

Assuming you stored the content of listing 2.5 in a file called docker-compose.yaml, it's straightforward to bring up the stack using the following code:

```
$ docker-compose -f docker-compose.yaml up
Creating network "logs_loki" with the default driver
Pulling loki (grafana/loki:2.4.0)...
2.4.0: Pulling from grafana/loki
...
Status: Downloaded newer image for grafana/promtail:2.4.0
Creating logs_loki_1     ... done
```