want to use those tools and require that those HTML components be included in your application. For instance, let's build a modal dialog box into which we can put the numbers associated with the teams. Say we want to see the stats on our teams—one of the best ways to do this is to build a dialog box that pops up as you click each team. A modal dialog is another way of referring to that "floating" area that typically only shows up when you click an element. We can write only the HTML we need for the table itself in a separate file.

Listing 3.4 modal.html

```
<table>
    <tr>
        <th>Statistics</th>
    </tr>
    <tr><td>Team Name</td><td class="data"></td></tr>
    <tr><td>Region</td><td class="data"></td></tr>
    <tr><td>Wins</td><td class="data"></td></tr>
    <tr><td>Losses</td><td class="data"></td></tr>
    <tr><td>Draws</td><td class="data"></td></tr>
    <tr><td>Points</td><td class="data"></td></tr>
    <tr><td>Goals For</td><td class="data"></td></tr>
    <tr><td>Goals Against</td><td class="data"></td></tr>
    <tr><td>Clean Sheets</td><td class="data"></td></tr>
    <tr><td>Yellow Cards</td><td class="data"></td></tr>
    <tr><td>Red Cards</td><td class="data"></td></tr>
</table>
```

And now we'll add CSS rules for the table and the div that we want to put it in. As you see in the following listing, we can use the `position` and `z-index` CSS styles because this is a traditional DOM element.

Listing 3.5 Update to d3ia.css

```
#modal {
  position:fixed;
  left:150px;
  top:20px;
  z-index:1;
  background: white;
  border: 1px black solid;
  box-shadow: 10px 10px 5px #888888;
}

tr {
  border: 1px gray solid;
}

td {
  font-size: 10px;
}
td.data {
  font-weight: 900;
}
```