```
            .attr("y1", yScale(d.min) - yScale(d.median))
            .attr("y2", yScale(d.min) - yScale(d.median))
            .style("stroke", "black")
            .style("stroke-width", "4px");

        d3.select(this)
            .append("rect")
            .attr("class", "range")
            .attr("width", 20)
            .attr("x", -10)
            .attr("y", yScale(d.q3) - yScale(d.median))
            .attr("height", yScale(d.q1) - yScale(d.q3))
            .style("fill", "white")
            .style("stroke", "black")
            .style("stroke-width", "2px");

        d3.select(this)
            .append("line")
            .attr("x1", -10)
            .attr("x2", 10)
            .attr("y1", 0)
            .attr("y2", 0)
            .style("stroke", "darkgray")
            .style("stroke-width", "4px");
});
```

The bottom bar of the min-max line

The offset so that the rectangle is centered on the median value

Median line doesn't need to be moved, because the parent <g> is centered on the median value

Listing 4.6 fulfills the requirement that we should also add an x-axis to remind us which day each box is associated with. This takes advantage of the explicit `.tickValues()` function you saw earlier. It also uses negative `tickSize()` and the corresponding offset of the `<g>` that we use to call the axis function.

Listing 4.6 Adding an axis using `tickValues`

```
    var xAxis = d3.svg.axis().scale(xScale).orient("bottom")
.tickSize(-470)
.tickValues([1,2,3,4,5,6,7]);
    d3.select("svg").append("g")
.attr("transform", "translate(0,470)")
.attr("id", "xAxisG").call(xAxis);
d3.select("#xAxisG > path.domain").style("display", "none");
```

A negative tickSize draws the lines above the axis, but we need to make sure to offset the axis by the same value.

Offsets the axis to correspond with our negative tickSize

Setting specific tickValues forces the axis to only show the corresponding values, which is useful when we want to override the automatic ticks created by the axis.

We can hide this, because it has extra ticks on the ends that distract our readers.

The end result of all this is a chart where each of our datapoints is represented, not by a single circle, but by a multipart graphical element designed to emphasize distribution.

The boxplot in figure 4.16 encodes not just the median age of visitors for that day, but the minimum, maximum, and distribution of the age of the majority of visitors. This expresses in detail the demographics of visitorship clearly and cleanly. It doesn't include the number of visitors, but we could encode that with color, make it available