Listing 4.7 tweetdata.csv

```
day,tweets,retweets,favorites
1,1,2,5
2,6,11,3
3,3,0,1
4,5,2,6
5,10,29,16
6,4,22,10
7,3,14,1
8,5,7,7
9,1,35,22
10,4,16,15
```

First we pull this CSV in using `d3.csv()` as we did in chapter 2, and then we create circles for each datapoint. We do this for each variation on the data, with the `.day` attribute determining x position and the other datapoint determining y position. We create the usual x and y scales to draw the shapes in the confines of our canvas. We also have a couple of axes to frame our results. Notice that we differentiated between the three datatypes by coloring them differently.

Listing 4.8 Callback function to draw a scatterplot from tweetdata

```
d3.csv("tweetdata.csv", lineChart);
function lineChart(data) {

   xScale = d3.scale.linear().domain([1,10.5]).range([20,480]);
   yScale = d3.scale.linear().domain([0,35]).range([480,20]);

   xAxis = d3.svg.axis()
        .scale(xScale)
        .orient("bottom")
        .tickSize(480)
        .tickValues([1,2,3,4,5,6,7,8,9,10]);

   d3.select("svg").append("g").attr("id", "xAxisG").call(xAxis);

   yAxis = d3.svg.axis()
        .scale(yScale)
        .orient("right")
        .ticks(10)
        .tickSize(480);

   d3.select("svg").append("g").attr("id", "yAxisG").call(yAxis);

   d3.select("svg").selectAll("circle.tweets")
        .data(data)
        .enter()
        .append("circle")
        .attr("class", "tweets")
        .attr("r", 5)
        .attr("cx", function(d) {return xScale(d.day)})
        .attr("cy", function(d) {return yScale(d.tweets)})
        .style("fill", "black");
```

Our scales, as usual, have margins built in.

Fixes the ticks of the x-axis to correspond to the days

Each of these uses the same dataset, but bases the y position on tweets, retweets, and favorites values, respectively.