```
    var xScale = d3.scale.linear().domain([0, 10]).range([0, 500]);
    var yScale = d3.scale.linear().domain([0, 100]).range([500, 0]);
    var movieColors = d3.scale
      .category10(["movie1","movie2","movie3","movie4","movie5","movie6"]);
    var stackArea = d3.svg.area()
        .interpolate("basis")
        .x(function(d) { return xScale(d.x); })
        .y0(function(d) { return yScale(d.y0); })
        .y1(function(d) { return yScale(d.y0 + d.y); });
    for (x in incData[0]) {
      if (x != "day") {
        var newMovieObject = {name: x, values: []};
        for (y in incData) {
          newMovieObject.values.push({
                x: parseInt(incData[y]["day"]) ,
                y: parseInt(incData[y][x])
          });
        };
        stackData.push(newMovieObject);
      };
    };
    stackLayout = d3.layout.stack()
       .offset("silhouette")
       .order("inside-out")
       .values(function(d) { return d.values; });
    d3.select("svg").selectAll("path")
       .data(stackLayout(stackData))
       .enter().append("path")
       .style("fill", function(d) {return movieColors(d.name);})
       .attr("d", function(d) { return stackArea(d.values); });
  };
```

We want to skip the day column, because, in this case, the day becomes our x value.

For each movie, we create an object with an empty array named "values".

Fill the "values" array with objects that list the x coordinate as the day and the y coordinate as the amount of money made by a movie on that day.

After the initial dataset is reformatted, the data in the object array is structured so that the stack layout can deal with it:

```
[
{"name":"movie1","values":[{"x":1,"y":20},{"x":2,"y":18},{"x":3,"y":14},{"x":
     4,"y":7},{"x":5,"y":4},{"x":6,"y":3},{"x":7,"y":2},{"x":8,"y":0},{"x":9,
     "y":0},{"x":10,"y":0}]},
{"name":"movie2","values":[{"x":1,"y":8},{"x":2,"y":5},{"x":3,"y":3},{"x":4,"
     y":3},{"x":5,"y":3},{"x":6,"y":1},{"x":7,"y":0},{"x":8,"y":0},{"x":9,"y"
     :0},{"x":10,"y":0}]}
...
```

The x value is the day, and the y value is the amount of money made by the movie that day, which corresponds to thickness. As with other layouts, if we didn't format our data this way, we'd need to adjust the `.x()` and `.y()` accessors to match our data names for those values. One of the benefits of formatting our data to match the expected data model of the layout is that the layout function is very simple:

```
stackLayout = d3.layout.stack()
.values(function(d) { return d.values; });
```

Function chains on the newly created stack() layout function